



Model	SH-NVR-4	
Camera Input	4CH POE NVR	
Housing	J	
Video	Input	4CH 1080P (PoE)
	Output	Max. 1920 x 1080 1HDMI with Audio and 1 VGA
Audio	Input	1 RCA
	Output	1 RCA
System	Operation System	Embedded Linus OS
	SATA Devices	Max. 1 X SATA Device (HDD X1)
	External HDD	N/A
	Sensor In (NO, NC)/ Relay Out	Sensor-in x 4; Relay-out x 1
	Serial Interface	RS-485
	USB 2.0 Ports	USB 2.0 X 2
	Dimension (mm)	280(W)x51(H)x203(D)
	Weight (w/o HDD/DVDRW)	1.03 KG
Display	Power Supply	DC 48V 1.25A 60W
	Power Rating	Adapter 110/220V
	Split Screen	1,4, SEQ.
Recording	Auto Channel Switching	Switching time: 1-99 sec.
	Mode	Zoom (x2~x5), PIP, Auto SEQ.
	Compression	H.264 High Profile
Playback	Recording Throughput (60Hz/50Hz IP Camera)	4 CH, each 1280 * 720 @ 30/25 fps; 1920 * 1080 @ 30/25 fps
	Mode	Continuous, Even, Schedule
Network	Search Mode	Date/time, Event
	Snapshot	YES
Backup	Network Interface	10/100 Ethernet
	Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS, FTP, SMTP
	Onvif	YES
	Remote Software	SoCatch, IE Browser, iCMS Pro
	Account	1 Admin + 10 Users
Alarm	Mobile Device	Windows Phone 7.8, iPhone, iPad, Android
	Interface	USB 2.0
	Audio Backup	YES
OSD & DVR Control	Backup Type	Network, ext. USB flash device , SATA optical DVD..etc.
	Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)
	Multi-Language	Supported
	USB Mouse	YES
	Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)
Operating Temperature	System Upgrade	USB Flash Drive, Iwatch DVR
	Operating Temperature	-10°C ~ +55°C (14°F ~ 131°F)
	Operating Humidity	10%~80%

All specifications are subject to change without notice.