

# **Secure The World With You**

**NVR** 



4K Output HD IPC

DDNS Network

ork PTZ

MIC



USB Mouse

e E-mail



AI-NVR16-8P 4K series are 16 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P high definition PoE NVRs, which adopt the most advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system.

Audio

AI-NVR16-8P 4K series integrate with 8 PoE network ports and support 8 CH IPC direct connection to NVR , simultaneous 16 CH playback, and 4K high definition display. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.



STD



shieldcctv.com For more information, please visit our website

#### Shield Technology Inc.

## AI-NVR16-8P 4K 8MP/5MP/4MP/3MP/1080P/ 960P/720P HD PoE NVR

#### SPECIFICATIONS

| Model            |   | AI-NVR16-8P 4K   |
|------------------|---|--|
| System           | Compression                               | Standard H.265/H.264   |
|                  | os  | Embedded Linux   |
| Video            | Network Input                             | 16CH IPC input   |
|                  | Network<br>Bandwidth                      | 160Mbps/160Mbps (access/transfer)  |
|                  | Network Access<br>Format                  | 8MP/5MP/4MP/3MP/1080P/960P/720P@25/30fps   |
|                  | Output                                    | HDMI × 1 : 3840 × 2160 / 1920 × 1080 / 1280 × 1024 / 1024 × 76<br>VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768             |
|                  | Network Input                             | 16 CH IPC audio input  |
| Audio            | 2-way Audio                               | RCA × 1  |
|                  | Local Output                              | RCA × 1  |
| Record           | Record Stream                             | Dual stream recording  |
|                  | Resolution                                | 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P  |
|                  | Mode                                      | Manual, timer, motion, sensor  |
| Playback         | Simultaneous<br>Playback                  | Max 16 CH  |
|                  | Search                                    | Time slice / time / event / tag search   |
|                  | Smart Search                              | Highlighted color to display the camera record in a certain period of time, different colors refers to different record events |
|                  | Function                                  | Play, pause, FF, FB, digital zoom, etc.  |
| Alarm            | Mode                                      | Manual, sensor, motion, exception  |
|                  | Input                                     | 8 CH local alarm input,<br>support 8CH IPC alarm input   |
|                  | Output                                    | 4 CH   |
|                  | Triggering                                | Record, snap, preset, e-mail, etc.   |
| Face             | Channel                                   | 16 CH  |
|                  | Face Picture<br>Database                  | 16 libraries<br>10000 Face Pictures  |
|                  | Computing<br>Capability                   | 240 pictures / minute  |
|                  | Face Picture<br>Search                    | Search by picture is supported   |
|                  | Database<br>Management                    | Add, modify, delete and search face pictures   |
|                  | Face Picture<br>Adding                    | Add face pictures through APP, WEB and local PC  |
|                  | External face<br>picture<br>enrollment    | Resolution : 64 x 64 $\sim$ 1920 x 1080<br>Size : less than 200KB<br>Format : jpg  |
|                  | Face Picture<br>Comparison                | Support allow list and block list alarm  |
|                  | Face Trace                                | Yes  |
|                  | Map of<br>Face Trace                      | Reolution : 600 x 300 ~ 3840 x 2160<br>Size : within 200KB<br>Format : jpg   |
|                  | Statistic Graph<br>of Face<br>Information | Bar graph, pie chart   |
|                  | Statistic Mode<br>of Face<br>Information  | Statistics by day, week, month, quarter as well as customized time period  |
| Network          | Interface                                 | RJ 45 1000 Mbps × 1  |
|                  | PoE Port                                  | RJ 45 × 8  |
|                  | Protocol                                  | TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP  |
|                  | Web Client                                | Multiple users online  |
| Mobile<br>Device | OS  | iOS, Andriod   |
| Storage          | HDD                                       | SATA × 2, max 10T per HDD  |

| Backup | Local Backup         | U disk, USB mobile HDD   |
|--------|----------------------|--|
|        | Network Backup       | Yes  |
| Port   | RS 485               | RS485 × 2, connect to PTZ or keyboard  |
|        | USB                  | USB 2.0 × 1 , USB 3.0 × 1 ( one in the front panel and the other in the rear panel ) |
|        | Remote<br>Controller | Optional   |
| Others | Power Supply         | DC48V/2.5A   |
|        | Consumption          | ≤ 15W ( without HDD )  |
|        | Dimensions<br>(mm)   | 380 × 268 × 52 ( W × D × H )   |
|        | Work<br>Environment  | -10 ~ 50 °C , 10% ~ 90% humidity   |
|        |                      |  |

#### Features

- Support 16 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback : 16 CH simultaneous playback
- Search : time slice, time, event (manual, sensor, motion), tag search
- Support face detection and comparison
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- 8 PoE network ports, support IPC direct connection to NVR; support PoE power supply
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS

### DIMENSIONS



