



SPECIFICATION	
Model	IPBZ-22812VLW
Camera	
Image Sensor	1/2.9" Progressive Scan CMOS Sensor
Horizontal Resolution	2MP
Compression	H.264/H.265
S/N Ratio	60db
PTZ	
Horizontal Rotation Speed	30°/S
Horizontal Rotation Range	0°~180°
Tilt Rotation Speed	25°/S
Tilt Rotation Range	-45°~40°
Preset Points	255
Guard Tours	8 groups
Guard Points	Max.20 points
Lens	
Focus Length	3.35-10.05mm F1.7-F3.0
Focus Control	4X Optical Zoom
Night Vision	
Infrared LED	Φ 35x6PCS
IR Range	30m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support PROFILE S,PROFILE G,PROFILE T)
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	1920*1080@30fps
Main Stream2	1280*720@30fps
Main Stream3	/
Main Stream4	/
Main Stream5	/
Main Stream6	/
Sub Stream1	720*480@30fps
Sub Stream2	352*288@30fps
Sub Stream3	/
Sub Stream4	/
Interface	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	Optional
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	39.6x19.6x16(cm)
Weight	1.35Kgs