



SPECIFICATION

Model	IPZ-20X
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H.265
S/N Ratio	60db
PTZ	
Horizontal Rotation Speed	200°/sec
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	100°/sec
Tilt Rotation Range	0°~93°
Preset Points	255
Guard Tours	8 groups
Guard Points	Max 20 points
Lens	
Focus Length	5.9-94.4mm F1.8-F3.9
Focus Control	20X Optical Zoom
Night Vision	
Infrared LED	Φ 35x6PCS IR LEDS + 2PCS Laser LED
IR Range	120m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support PROFILE S,PROFILE G,PROFILE T)
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	5MP(2592*1944)@20fps
Main Stream2	4MP(2560*1440)@25fps
Main Stream3	1080P(1920*1080)@30fps
Main Stream4	720P(1280*720)@30fps
Main Stream5	/
Main Stream6	/
Sub Stream1	D1(720*480)@20fps
Sub Stream2	CIF(352*288)@20fps
Sub Stream3	/
Sub Stream4	/
Interface	
Audio	Optional
Alarm	/
SD Card Slot	Optional
POE	Optional
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V/4A or PoE
Lightning Protection	Transient voltage 6000V
Dimension	31x31x44(cm)
Weight	2.28Kgs